PURE

3.8 CFM @ 90 PSI - 26 GALLON **ELECTRIC AIR COMPRESSOR**

MODEL: PPAC2026

- 2.0 HP motor set up for 120v operation drawing 14.2 amps.
- Oil lubricated pump that is easy to access for maintenance when needed.
- Cast iron cylinder increases the life of the pump.
- Pressure switch is set to cut-in at 95 PSI then cut-off at 125 PSI.
- Twin air gauges. One shows air pressure that is built up in the tank. The second gauge shows air pressure going into the air line, which can be adjusted with the regulator as needed.
- Vertical 26 gallon tank takes minimal floor space and has flat free tires making it easy to move.
- 10" flat free wheels that allow for easy movement around workspace.
- Designed and constructed for residential and shop applications.



MOTOR

HORSE POWER: 2.0 AMPS: 14.2 VOLTS: 120 DUTY CYCLE: 100% DB RATING: 75 @ 7M RPM: 3400

PUMP SPECS

TYPE: RECIPROCATING CFM @ 40 PSI: 4.8 CFM @ 90 PSI: 3.8 MAX PSI 125 STAGE: **SINGLE** OIL TYPE: **SAE-30 NON-DETERGENT**

DUTY CYCLE: 50% 2850

FRAME

TANK SIZE: **26 GALLONS**

POWDER COATED STEEL MATERIAL: FITTINGS: **1 INDUSTRIAL COUPLER**

10" FLAT FREE WHEELS: TANK DRAIN: **BALL VALVE**

BOXED SIZE

RPM:

LxWxH: 21" x 19.5" x 49.25" WEIGHT: 108 LBS

UNIT SIZE



UNIT WEIGHT: 100 LBS

WARRANTY

AIR COMPRESSOR: 1 YEAR

UPC: 777987370623